



JOJNIYA EXPLOSIVES PRIVATE LIMITED
KANGANI, BHILWARA, RAJASTHAN
TECHNICAL DATA SHEET

TIGER POWER BOOST 90

Description :

Tiger Power Boost 90 is a high strength, robust detonator sensitive emulsion explosive. The explosive is grey in color with a firm putty-like consistency. It is packaged in plastic film with wire clips.

Application :

Tiger Power Boost 90 is a water-resistant packaged explosive designed to deliver high energy .It can be used in surface and non gassy underground mining and general blasting.

Tiger Power Boost 90 is a preferred packaged explosive where ground conditions require the application of high energy explosives to achieve adequate fragmentation and movement. The high detonation velocity and the robust nature of Tiger Power Boost 90.Tiger Power Boost 90 cartridges are packaged in film, which readily splits during tamping to maximize coupling and bulk strength within a blast hole.

The high resistance of Tiger Power Boost 90 to dynamic desensitization makes it the preferred explosive for use in tunneling, quarrying, shaft sinking, and other extreme blasting environments.

Key Benefits

- Tiger Power Boost 90 is a maximum energy emulsion formulation with high pre-compression resistance.
- This gives excellent blast results in the toughest ground even with tight drilling patterns as found in shaft sinking and other extreme blasting environments.
- Tiger Power Boost 90 reduces post-blast

fumes and improves turn around.

Recommendations for Use:

Blast hole Charge Length

Tiger Power Boost 90 is suitable for use in blast holes of any practical depth providing contained water does not exceed 20m depth.

Reactive Ground and Ground Temperature

Reactive Ground—Tiger Power Boost 90 is not suitable for use in the ground containing reactive sulphides

Elevated Temperature— Tiger Power Boost 90 is suitable for use in ground temperatures from 0°C up to 55°C.

However, if your application requires you to operate at elevated temperature, above 55°C please contact your JEPL Technical Representative in advance for further information about product compatibility, sleep time and use.

Technical Properties :-

Density	1.15 ± 0.05 g/cc
Relative Weight Strength as compared to ANFO @0.8 g/cc.	125%
Relative Bulk Strength as compared to ANFO @ 0.8g/cc	169%
Minimum Velocity of Detonation ⁽²⁾	3800 m/s



JOJNIYA EXPLOSIVES PRIVATE LIMITED
KANGANI, BHILWARA, RAJASTHAN
TECHNICAL DATA SHEET

Priming and Initiation

Tiger Power Boost 90 at temperatures higher than 0°C can be reliably initiated by an electric No.8*, non electric detonator (min. 8* strength), Detonating cord 5 g/m may also be used to initiate Tiger Power Boost 90, however, detonating cords of charge mass lower than 5 g/m are not recommended for initiation of Tiger Power Boost 90.

Charging

In small diameter blast holes, maximum energy per meter of blast hole can be achieved by tamping the explosive with a wooden tamping rod appropriate to the hole diameter. No metal instrument should be used to tamp explosives. The primer cartridge containing a detonator must not be tamped.

Sleep-Time within Blast holes

Tiger Power Boost 90 is highly water-resistant, which minimizes leaching and reduces environmental impact.

Undamaged, 'Tiger Power Boost 90' may be charged and fired several days later (provided the product remains within its recommended shelf life).

If the packaging of the explosives is damaged, the sleep time in the blast hole is influenced by the extent of damage to the packaging and by the nature of any water present slitting of cartridges, the explosive will give good performance after two weeks of immersion depending on the hole conditions.

An JEPL Technical Representative should be consulted if special conditions exist.

Product Quality

JEPL's packaged explosives are manufactured and loaded using an ISO 9001.

Packaging

Both the Tiger Power Boost 90 packaging cases and film are color highlighted in red. It is packaged in white plastic film with colored printing. Each box contains nominally 25kg of the product with standard cartridge sizes and counts as follows:

Diameter (mm)	Nominal Length (mm)	Nominal Mass (g)	Cartridges per Box
40	300	390	200

Storage and Handling

Product Classification

Authorized Name : Tiger Power Boost 90

Shipping Name : Explosive blasting type E

UN No. : 0241

Classification : 1.1D

As per Indian Explosives rules, Tiger Power Boost 90 is a class 2 explosive. All regulations pertaining to the handling and use of such explosives apply.

Storage

Store Tiger Power Boost 90 in a suitably licensed magazine for Class 1.1D/Class 2 explosives. The cases should be stacked in the manner designated on the cases. Tiger Power Boost 90 has a storage life of up to 6 months in an approved magazine; however, exposure to hot or cold extremes may cause the product to



JOJNIYA EXPLOSIVES PRIVATE LIMITED
KANGANI, BHILWARA, RAJASTHAN
TECHNICAL DATA SHEET

deteriorate prematurely. Tiger Power Boost 90 is best stored at temperatures above 0°C.

Disposal

Disposal of explosive materials can be hazardous. Methods of safe disposal of explosives may vary depending on the user's situation. Please contact an JEPL Technical Services Representative for information on safe practices.

Safety

The post-detonation fume characteristics of Tiger Power Boost 90 make it suitable for non gassy underground and surface blasting applications. Users should ensure that adequate ventilation is provided prior to re-entry into the blast area.

Tiger Power Boost 90 can be initiated by extreme of shock, friction or mechanical impact. As with all explosives, Tiger Power Boost 90 should be handled and stored with care. Tiger Power Boost 90 does not burn easily, but it must be kept clear of flame and excessive heat.

Explosives based on Ammonium Nitrate such as Tiger Power Boost 90 may react with sulphides in the ground and create potentially hazardous situations. JEPL accepts no responsibility for any loss or liability arising from the use of the product in the ground containing sulphides or other reactive material.

DISCLAIMER :-

All rights reserved. All information contained in this document is provided for informational purposes only and is subject to change without notice. Since the JEPL cannot anticipate or control the conditions under which this information and its products may be used, each user should review the information in the specific context of the intended application . To the

maximum extent permitted by law, the JEPL specifically disclaims all warranties express or implied warranties of merchant ability or fitness for a particular purpose. The JEPL specifically disclaims, and will not be responsible for, any liability or damages resulting from the use or reliance upon the information in this document.

TIGER Brand name Power Boost 90 is a trademark of JOJNIYA Explosives Pvt. Ltd.

